

deSoutter
MEDICAL





sternudrive™

www.de-soutter.com

DB BATTERY STERNUM SAWS

The DBC-470 has a unique active damping system which reduces vibration by 30% and noise by up to 40%. A single piece micro adjustable blade guard provides optimum control of the cutting direction for primary sternotomies.



Simple twist and click sternum blade guard for quick and efficient use



Sternum guard
Order code 16490

Model	Order code	Speed cpm	Stroke
DBC-470	1290224	0 - 14000	3.7 mm
DBR-470	1291664	0 - 15000	-
DBR-700	1290884	0 - 13500	-

MBC MODULAR BATTERY STERNUM SAW

The De Soutter Medical MBC sternudrive lite™ is a powerful, yet versatile modular sternum saw system for primary, revision and paediatric surgery. The handpiece is powered by either sterile or aseptic Li-ion batteries, assuring class leading power to weight ratio.



MBC-709
sternudrive Lite™
Handpiece



*Oscillating
sagittal
sternum saw*
Uses S87 saw blades











*Oscillating
paediatric sagittal
sternum saw*
Uses S88-9XX saw blades



*Reciprocating
sternum saw*
Uses S84-4XX saw blades



Sternum guard

	Model	Description	Order code	Speed cpm/rpm
	MBC-709	Modular handpiece	1291554	0 - 13000
	CQ-709	Reciprocating sternum saw Sternum guard	18380 16490	0 - 13000
	NQ-709	Oscillating paediatric sternum saw	18450	0 - 13000
	KQ-709	Oscillating sagittal sternum saw	17650	0 - 13000
	DQ-709	0.5 - 7.4 mm (1/4") keyed drill Cannulation 4.4 mm	19380	0 - 1300
	DQ-709	Small A.O. Synthes/ASIF drill Cannulation 2.1 mm	19430	0 - 1300
	OQ-709	Oscillating sternum saw Blade tightening wrench	18420 190723	0 - 13000
	WQ-709	Wire driver 0.7 - 4.0 mm	19390	

DP AIR STERNUM SAWS

DPC-470 offers the same innovative functionality as the battery sternum saw. A single piece, twist and click, micro adjustable blade guard provides quick and efficient use with optimum control of the cutting direction. For revision sternotomies, the DPX-170 oscillating saw handpiece is also offered.







DPC-470
for primary sternotomies

Wash assist air hose



This hose system is recommended where machine washing of air hoses is required. By releasing the probe end from the hose, which is retained on the hose via the rubber strap, the two hose ends can be joined and sealed prior to machine washing.



Probe end	Model	3 m hose	4 m hose	5 m hose
			Order code	
	DPC-470	13300	13400	13500
	DPX-170	13000	13100	13200
	DPC-470	13310	13410	13510
	DPX-170	13010	13110	13210
	DPC-470	13330	13430	13530
	DPX-170	13030	13130	13230
	DPC-470	13320	13420	13520
	DPX-170	13020	13120	13220

Air inlet washing cap.




Order code 9950 for DPC-470
Order code 608073 for DPX-170

Other probe connectors are available on request.

Model	Order code	Speed	Stroke	Operating pressure	
DPC-470	226614	0 - 16000 cpm	3.7 mm	6 - 7 bar	
Model	Order code	Speed	Oscillating arc	Operating pressure	
DPX-170	223224	0 - 13000 cpm	6°	6 - 7 bar	


SAW BLADES

RECIPROCATING BLADES FOR DBC-470, DPC-470 AND CQ-709




Blade Order code	Blade thickness	Cut thickness	Tooth pitch
S84-400	0.8 mm	1.2 mm	1.4 mm (18 TPI) Uni directional cut
S84-401	0.8 mm	1.2 mm	1.4 mm (18 TPI) Bi directional cut
S84-402	0.6 mm	1.2 mm	1.4 mm (18 TPI) Uni directional cut


OSCILLATING BLADES FOR DPX-170




S81-101
S81-102



S81-200
S81-201
S81-202




S81-105
S81-106



S81-107


Blade Order code	Blade thickness	Cut thickness	Tooth pitch	Useable length	Blade width
S81-107	0.5 mm	1.0 mm	1.3 mm (20 TPI)	20 mm	24 mm
S81-106	0.5 mm	1.0 mm	1.6 mm (16 TPI)	16 mm	25 mm
S81-105	0.5 mm	1.0 mm	1.8 mm (14 TPI)	23 mm	32 mm
S81-101	0.5 mm	1.0 mm	1.8 mm (14 TPI)	23 mm	32 mm
S81-102	0.5 mm	1.0 mm	1.5 mm (17 TPI)	29 mm	38 mm
S81-200	0.5 mm	1.0 mm	1.4 mm (18 TPI)	43 mm	57 mm
S81-201	0.5 mm	1.0 mm	1.3 mm (20 TPI)	18 mm	32 mm
S81-202	0.5 mm	1.0 mm	1.6 mm (16 TPI)	36 mm	50 mm

OSCILLATING BLADES FOR DBR-470 AND NQ-709




Blade Order code	Blade thickness	Cut thickness	Tooth pitch	Useable length	Blade width
S88-908	0.6 mm	0.6 mm	1.4 mm	19 mm	50 mm
S88-909	0.6 mm	0.6 mm	1.4 mm	19 mm	63 mm
S88-918	0.6 mm	0.6 mm	1.4 mm	25 mm	50 mm
S88-919	0.6 mm	0.6 mm	1.4 mm	25 mm	63 mm


OSCILLATING BLADES FOR DBR-700 AND KQ-709




S87-118
S87-119
S87-120



S87-121
S87-123



S87-112
S87-512



S87-113

Blade Order code	Blade thickness	Cut thickness	Tooth pitch	Useable length	Blade width
S87-112	0.6 mm	0.8 mm	1.9 mm	65 mm	50 mm
S87-113	0.6 mm	0.8 mm	1.9 mm	65 mm	50 mm
S87-118 Pediatric	0.51 mm	0.9 mm	1.4 mm	23 mm	50 mm
S87-119 Pediatric	0.51 mm	0.9 mm	1.4 mm	23 mm	63 mm
S87-120	0.51 mm	1.0 mm	1.6 mm	35 mm	82 mm
S87-121	0.51 mm	1.0 mm	1.6 mm	35 mm	82 mm
S87-123	0.51 mm	0.9 mm	1,4 mm	23 mm	50 mm
S87-512	0.6 mm	0.6 mm	2,1 mm	65 mm	50 mm

BATTERY CHARGERS AND BATTERIES





BC-700 Battery charger shown with aseptic batteries.

The BC-700 Battery Charger requires minimal user input. Simply insert battery and the BC-700 will charge, recover and recondition it to its optimum state.

The large touch-screen display with intuitive menu navigation, displays instant battery charge status and condition. Includes a multi-lingual display and other user settings.

The BC-700 also offers a **unique healthcheck facility**, profiling the condition of an individual battery, automatically reconditioning it to provide optimal capacity. Alternatively, a manual healthcheck can be easily selected.

The BC-700 Battery Charger accepts all De Soutter Medical batteries, ensuring total backwards compatibility.

Charger - Order code	Charger configuration	Charger module - Order code	For battery type
16230	4-off CA-703 charger modules	18120 	AB-703 AB-704
16220	4-off CA-700 charger modules	15750 	SB-703 SB-704

Without charger module fitted - Order code 15700
Charger modules can be quickly changed to suit the batteries being charged.

Mains power cordsets - 3 metres long. Please specify -
UK - Order code 8290 Euro - Order code 8300 US/Canada - Order code 8310
Australia/New Zealand - Order code 8320 Swiss - Order code 14700

SINGLE BAY CHARGERS



Model	Charger Order code	For battery type
BC-706	17990	SB-703/SB-704
BC-707	18000	AB-703
BC-708	18010	AB-704

LITHIUM ION BATTERIES

Why choose Lithium Ion battery technology

De Soutter Medical Lithium Ion batteries offer the surgical team and sterile services a number of tangible benefits over conventional battery technology.

- Li-Ion technology improves battery 'capacity to weight' ratio by around 25% when compared to equivalent NiMH or NiCad chemistries.
- Significantly extends the useable run time of the power tool.
- Eliminates 'memory effect' normally associated with other battery types.
- De Soutter Medical sterile Li-Ion technology readily withstands repeated machine washing and autoclaving.
- Unique **fuel gauge** incorporated within De Soutter Medical Li-Ion batteries allows the surgical team to instantly assess the battery capacity - both before and during use.



LITHIUM ION BATTERIES

LITHIUM ION STERILE BATTERIES



Model	Order code	Voltage MiNH	Capacity mAh
SB-703	17210	13.2	1100
SB-704	17220	13.2	2500

LITHIUM ION ASEPTIC BATTERIES



Aseptic Battery Model		Aseptic Housing Model		Aseptic Shield Model		Voltage MiNH	Capacity mAh
AB-703	17910	AH-703	18080	AS-703	18100	10.95V	2000
AB-704	17920	AH-704	18090	AS-704	18110	14.6V	2000

STERILISATION TRAYS AND CONTAINER

ASEPTIC SYSTEM



Tray with MBC-709 handpiece

Set up - optional tray contents	Container and tray	Tray only
1 off DBR-700 handpiece 1 off aseptic housing and shield	Order code 19170	Order code 19070
1 off DBR-470 or DBC-470 handpiece 1 off sternum guard (DBC-470 only) 1 off aseptic housing and shield	Order code 18210	Order code 18200
1 off MBC-709 handpiece 3 off attachments 1 off sternum guard 1 off aseptic housing and shield	Order code 19280	Order code 19300

STERILE SYSTEM



Tray with DBR-470 handpiece

Set up - optional tray contents	Container and tray	Tray only
1 off DBR-700 handpiece 1 off sterile battery	Order code 17890	Order code 17880
1 off DBR-470 or DBC-470 handpiece 1 off sternum guard (DBC-470 only) 1 off sterile battery	Order code 19270	Order code 19110
1 off MBC-709 handpiece 3 off attachments 1 off sternum guard 1 off sterile battery	Order code 19200	Order code 19100
1 off DPC-470 handpiece 1 off sternum guard	Order code 17160	Order code 17170
2 off SB-703 or SB-704 sterile batteries	Order code 17390	Order code 17400



Wire container for trays - Order code 19000

STERILE FILTERED CONTAINER

Order code 19370
Accepts aseptic and sterile trays.
Lid gasket - Order code 669903

UNITED STATES OF AMERICA
De Soutter Medical USA, Inc.
224 Rolling Hill Road, Suite 12A
 Mooresville, NC 28117
Tel: +1 (704) 655 9040
fax: +1 (704) 987 2035
Email: usa@de-soutter.com

UNITED KINGDOM (INTERNATIONAL HEAD OFFICE)
De Soutter Medical Limited
Halton Brook Business Park, Weston Road
Aston Clinton, Aylesbury, Bucks HP22 5WF
Tel: +44 (0) 1296 634 000
Fax: +44 (0) 1296 634 033
Email: info@de-soutter.com

AUSTRALIA
De Soutter Medical Australia Pty Ltd
2/12-14 Apollo Drive, Hallam
Victoria 3803
Tel: +61 (0) 3 9702 4441
Fax: +61 (0) 3 9702 4484
Email: australia@de-soutter.com

AUSTRIA
De Soutter Medical Austria
Zweigniederlassung Österreich
Dietrichsteingasse 10, A-3400 Klosterneuburg
Tel: +43 (0) 676 96 71 770
Fax: +43 (0) 2243 21 656
Email: austria@de-soutter.com

BELGIUM
De Soutter Medical Belgium
In De Bruel 30
3620 Lanaken
Tel: +32 (0) 89/47 15 37
Fax: +32 (0) 89/70 12 19
Email: belgium@de-soutter.com

FRANCE
De Soutter Medical France
949 Avenue du Parc des Expositions
33260 La Teste de Buch
Tel: +33 (0) 5 56 54 89 36
Fax: +33 (0) 9 70 61 37 60
Email: france@de-soutter.com

GERMANY
De Soutter Medical Deutschland
Bahnhofstraße 4
D-66625 Nohfelden
Tel: +49 (0) 68 52-99 12 46
Fax: +49 (0) 68 52-99 12 47
Email: deutschland@de-soutter.com

ITALY
De Soutter Medical Italia
Località Fornace SNC
27022 Casorate Primo - PV
Tel: +39 (0) 2 9009 4098
Fax: +39 (0) 2 9009 2673
Email: italy@de-soutter.com

NETHERLANDS
De Soutter Medical Nederland
Gelderlandhaven 2X
3433 PG Nieuwegein
Tel: +31 (0) 85 0491480
Fax: +31 (0) 85 0491489
Email: nederland@de-soutter.co

deSoutter For further information on De Soutter Medical powered instruments
MEDICAL and cast saw systems please contact the address in your area.